



# GARLOCK BEARINGS LTD



0.591 Inch | 15 Millimeter x 1.378 Inch | 35 Millimeter x 0.626 Inch | 15.9 Millimeter SKF 3202 A-2ZTN9/C3 Angular Contact Ball Bearings

Bearing No. 3202 A-2ZTN9/C3

3202 A-2ZTN9/C3 Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.072
Product Group	B00152
Enclosure	2 Metal Shields
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	24 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 15.9MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap Ring



## GARLOCK BEARINGS LTD

Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	5202 A-2ZTN9
Weight / LBS	0.147
B	0.626 Inch   15.9 Millimeter
d	0.591 Inch   15 Millimeter
D	1.378 Inch   35 Millimeter
bore diameter:	15 mm
cage material:	Fiberglass Reinforced Nylon
outside diameter:	35 mm
outer ring width:	15.9 mm
overall width:	0.6250 in
maximum rpm:	18000 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C3
precision rating:	Not Rated
closure type:	Double Shield
fillet radius:	0.6 mm
radial dynamic load capacity:	11.2 kN
series:	32
radial static load capacity:	6.8 kN