



GARLOCK BEARINGS LTD



2.559 Inch | 65 Millimeter x 4.724 Inch | 120
 Millimeter x 0.906 Inch | 23 Millimeter SKF 7213
 BECBY/W64 Angular Contact Ball Bearings

Bearing No. 7213 BECBY/W64

7213 BECBY/W64 Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap



GARLOCK BEARINGS LTD

	Ring; CB; Brass Cage; 40 Degree; 1 (Single); Univers
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7213 BECBY/W64
d	2.559 Inch 65 Millimeter
B	0.906 Inch 23 Millimeter
D	4.724 Inch 120 Millimeter
bore diameter:	65 mm
snap ring included:	Without Snap Ring
outside diameter:	120 mm
bearing material:	Chrome Steel
overall width:	23 mm
radial dynamic load capacity:	15624 lbf
contact angle:	40 °
radial static load capacity:	12814 lbf
row type & fill slot:	Single-Row Non-Fill Slot
operating temperature range:	0 ° F to 185 ° F
internal clearance:	C0
cage material:	Steel
bore type:	Round
finish/coating:	Uncoated
closure type:	Open
application:	Metal manufacturing, Paper mills, Steel mills – plate,



GARLOCK BEARINGS LTD

slab, strip, blast furnace, Overhead cranes, Food and beverage, Rock and stone conveyors, Shipyards Metal manufacturing Pap
