



GARLOCK BEARINGS LTD



2.559 Inch | 65 Millimeter x 4.724 Inch | 120 Millimeter x 1.5 Inch | 38.1 Millimeter SKF 3213 A-2Z/C3 Angular Contact Ball Bearings

Bearing No. 3213 A-2Z/C3

3213 A-2Z/C3 Bearing 2D drawings and 3D CAD models

| | |
|---------------------------------|---|
| Category | Angular Contact Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 1.588 |
| EAN | 7316573931294 |
| Product Group | B00152 |
| Enclosure | 2 Metal Shields |
| Flush Ground | No |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Double Row |
| Precision Class | ABEC 3 ISO P6 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Steel |
| Contact Angle | 30 Degree |
| Internal Clearance | C3-Loose |
| Number of Bearings | 1 (Single) |
| Inch - Metric | Metric |
| Long Description | 65MM Bore; 120MM Outside Diameter; 38.1MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 3 ISO P6; No Filling Slot; |



GARLOCK BEARINGS LTD

| | |
|-------------------------------|---|
| | No Snap Ring |
| Category | Angular Contact Ball Bearing |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 5213 A-2Z/C3 |
| Weight / LBS | 3.402 |
| d | 2.559 Inch 65 Millimeter |
| B | 1.5 Inch 38.1 Millimeter |
| D | 4.724 Inch 120 Millimeter |
| bore diameter: | 65 mm |
| radial static load capacity: | 73.5 kN |
| outside diameter: | 120 mm |
| cage material: | Steel |
| overall width: | 1.5000 in |
| outer ring width: | 38.1 mm |
| contact angle: | 30 ° |
| maximum rpm: | 4800 RPM |
| row type & fill slot: | Double-Row Non-Fill Slot |
| finish/coating: | Uncoated |
| internal clearance: | C3 |
| precision rating: | Not Rated |
| closure type: | Double Shield |
| fillet radius: | 1.5 mm |
| radial dynamic load capacity: | 80.6 kN |
| series: | 32 |