



GARLOCK BEARINGS LTD



2.559 Inch | 65 Millimeter x 4.724 Inch | 120
 Millimeter x 1.5 Inch | 38.1 Millimeter SKF 3213
 A-2RS1/C3MT33 Angular Contact Ball Bearings

Bearing No. 3213 A-2RS1/C3MT33

3213 A-2RS1/C3MT33 Bearing 2D drawings and 3D
 CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.624
Product Group	B00152
Enclosure	2 Seals
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	30 Degree
Internal Clearance	C3-Loose
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	65MM Bore; 120MM Outside Diameter; 38.1MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C3-Loose;



GARLOCK BEARINGS LTD

	Steel Cage; 30 Degree; 1 (Single)
Other Features	NBR Contact Seal MT33-Lithium Soap Thickener Grease
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	3213 A-2RS1/C3MT33
Weight / LBS	3.578
D	4.724 Inch 120 Millimeter
B	1.5 Inch 38.1 Millimeter
d	2.559 Inch 65 Millimeter
bore diameter:	65 mm
operating temperature range:	-40 to +210 ° F
outside diameter:	120 mm
outer ring width:	38.1 mm
overall width:	1.5000 in
maximum rpm:	3600 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C3
precision rating:	Not Rated
closure type:	Double Seal
fillet radius:	1.5 mm
radial dynamic load capacity:	80.6 kN
series:	32
radial static load capacity:	73.5 kN



GARLOCK BEARINGS LTD