



# GARLOCK BEARINGS LTD



7212 BECBP Bearing 2D drawings and 3D CAD models

## 60 mm x 110 mm x 22 mm SKF 7212 BECBP Angular Contact Ball Bearings

Bearing No. 7212 BECBP

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.78
EAN	7316577292209
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap



## GARLOCK BEARINGS LTD

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7212 BECBP
Weight / LBS	1.713
B	0.866 Inch   22 Millimeter
D	4.331 Inch   110 Millimeter
d	2.362 Inch   60 Millimeter
bore diameter:	60 mm
radial static load capacity:	50 kN
outside diameter:	110 mm
cage material:	Nylon
overall width:	22 mm
outer ring width:	22 mm
contact angle:	40 °
maximum rpm:	7500 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1.5 mm
radial dynamic load capacity:	61 kN
series:	72
d	60 mm



## GARLOCK BEARINGS LTD

D	110 mm
B	22 mm
d <sub>1</sub>	79.6 mm
d <sub>2</sub>	69.32 mm
D <sub>1</sub>	91.55 mm
a	47 mm
r <sub>1,2</sub> min.	1.5 mm
r <sub>3,4</sub> min.	1 mm
d <sub>a</sub> min.	69 mm
D <sub>a</sub> max.	101 mm
D <sub>b</sub> max.	104 mm
r <sub>a</sub> max.	1.5 mm
r <sub>b</sub> max.	1 mm
Basic dynamic load rating C	61 kN
Basic static load rating C <sub>0</sub>	50 kN
Fatigue load limit P <sub>u</sub>	2.12 kN
Reference speed	7000 r/min
Limiting speed	7500 r/min
Calculation factor A	0.0344
Calculation factor k <sub>r</sub>	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y <sub>0</sub>	0.26
Calculation factor Y <sub>2</sub>	0.57
Calculation factor X	0.57
Calculation factor Y <sub>0</sub>	0.52
Calculation factor Y <sub>1</sub>	0.55
Calculation factor Y <sub>2</sub>	0.93
Mass bearing	0.8 kg