



GARLOCK BEARINGS LTD



30 mm x 72 mm x 19 mm SKF QJ 306 MA Angular Contact Ball Bearings

Bearing No. QJ 306 MA

QJ 306 MA Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.42
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	35 Degree 4 Point
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	30MM Bore; 72MM Outside Diameter; 19MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Other Features	Split Inner Race



GARLOCK BEARINGS LTD

Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	QJ 306 MA
Weight / LBS	0.926
D	2.835 Inch 72 Millimeter
d	1.181 Inch 30 Millimeter
B	0.748 Inch 19 Millimeter
inside diameter:	30 mm
precision rating:	ABEC 1 (ISO Class Normal)
outside diameter:	72 mm
cage material:	Brass
overall width:	19 mm
maximum rpm:	17000 RPM
internal clearance:	C0
finish/coating:	Uncoated
closure type:	Open
outer ring width:	19 mm
radial dynamic load capacity:	53 kN
fillet radius:	1 mm
radial static load capacity:	41.5 kN
series:	QJ
d	30 mm
D	72 mm
B	19 mm
d ₁	40.5 mm
D ₁	58.2 mm



GARLOCK BEARINGS LTD

a	36 mm
$r_{1,2}$ min.	1.1 mm
d_a min.	37 mm
D_a max.	65 mm
r_a max.	1 mm
Basic dynamic load rating C	53 kN
Basic static load rating C_0	41.5 kN
Fatigue load limit P_u	1.76 kN
Limiting speed	17000 r/min
Calculation factor A	0.00508
Calculation factor e	0.95
Calculation factor X	0.6
Calculation factor Y_0	0.58
Calculation factor Y_1	0.66
Calculation factor Y_2	1.07
Mass bearing	0.42 kg