



# GARLOCK BEARINGS LTD



7311 BECBJ Bearing 2D drawings and 3D CAD models

## 55 mm x 120 mm x 29 mm SKF 7311 BECBJ Angular Contact Ball Bearings

Bearing No. 7311 BECBJ

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.487
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	55MM Bore; 120MM Outside Diameter; 29MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; CB; Steel Cage; 40



## GARLOCK BEARINGS LTD

	Degree; 1 (Single); Univers
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7311 BECBJ
B	1.142 Inch   29 Millimeter
d	2.165 Inch   55 Millimeter
D	4.724 Inch   120 Millimeter
bore diameter:	55 mm
radial static load capacity:	60 kN
outside diameter:	120 mm
outer ring width:	29 mm
overall width:	29 mm
maximum rpm:	6700 RPM
contact angle:	40 °
finish/coating:	Uncoated
row type & fill slot:	Single-Row Non-Fill Slot
precision rating:	Not Rated
internal clearance:	C0
fillet radius:	2 mm
closure type:	Open
series:	73
radial dynamic load capacity:	85.2 kN
d	55 mm
D	120 mm
B	29 mm



## GARLOCK BEARINGS LTD

$d_1$	80.3 mm
$d_2$	66.66 mm
$D_1$	96.6 mm
a	51 mm
$r_{1,2}$ min.	2 mm
$r_{3,4}$ min.	1 mm
$d_a$ min.	66 mm
$D_a$ max.	109 mm
$D_b$ max.	114 mm
$r_a$ max.	2 mm
$r_b$ max.	1 mm
Basic dynamic load rating C	85 kN
Basic static load rating $C_0$	60 kN
Fatigue load limit $P_u$	2.55 kN
Reference speed	7000 r/min
Limiting speed	7000 r/min
Calculation factor A	0.0574
Calculation factor $k_r$	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor $Y_0$	0.26
Calculation factor $Y_2$	0.57
Calculation factor X	0.57
Calculation factor $Y_0$	0.52
Calculation factor $Y_1$	0.55
Calculation factor $Y_2$	0.93
Mass bearing	1.4 kg