



# GARLOCK BEARINGS LTD



NU 232 ECML/C3 Bearing 2D drawings and 3D CAD models

6.299 Inch | 160 Millimeter x 11.417 Inch | 290 Millimeter x 1.89 Inch | 48 Millimeter SKF NU 232 ECML/C3 Cylindrical Roller Bearings

Bearing No. NU 232 ECML/C3

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	14.473
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	160MM Bore; Straight Bore Profile; 290MM Outside Diameter; 48MM Width; Brass Cage Material; RBEC 1   ISO P0; Single Row;



## GARLOCK BEARINGS LTD

	Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NU 232 ECML/C3
Weight / LBS	31.879
B	1.89 Inch   48 Millimeter
D	11.417 Inch   290 Millimeter
d	6.299 Inch   160 Millimeter
bore diameter:	160 mm
static load capacity:	680 kN
outside diameter:	290 mm
precision rating:	Not Rated
overall width:	48 mm
maximum rpm:	2600 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Brass
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	48 mm
operating temperature range:	Maximum of +300 ° F
fillet radius:	2.5 mm



## GARLOCK BEARINGS LTD

dynamic load capacity:	585 kN
series:	NU2