




GARLOCK BEARINGS LTD



9.449 Inch | 240 Millimeter x 12.598 Inch | 320 Millimeter x 1.89 Inch | 48 Millimeter SKF NCF 2948 CV/C3 Cylindrical Roller Bearings

Bearing No. NCF 2948 CV/C3

NCF 2948 CV/C3 Bearing 2D drawings and 3D CAD models

| | |
|---------------------------|---|
| Category | Cylindrical Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 10.81 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | None |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C3-Loose |
| Retainer | No |
| Relubricatable | Yes |
| Inch - Metric | Metric |
| Other Features | Full Complement 2 Rib Inner Ring 1 Rib Outer Ring with Retaining Ring |
| Long Description | 240MM Bore; Straight Bore Profile; 320MM Outside Diameter; 48MM Width; RBEC 1 ISO P0; Single Row; Not Separable; No |



GARLOCK BEARINGS LTD

| | |
|------------------------------|--|
| | Snap Ring; Relubricatable; C3-Loose Internal Clearance; No Retainer |
| Category | Cylindrical Roller Bearing |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | NCF 2948 CV/C3 |
| Weight / LBS | 23.81 |
| D | 12.598 Inch 320 Millimeter |
| d | 9.449 Inch 240 Millimeter |
| B | 1.89 Inch 48 Millimeter |
| bore diameter: | 240 mm |
| static load capacity: | 1140 kN |
| outside diameter: | 320 mm |
| precision rating: | Not Rated |
| overall width: | 48 mm |
| maximum rpm: | 1100 RPM |
| flanges: | (2) Inner Ring, (1) Outer Ring |
| cage material: | No Cage |
| bore type: | Straight |
| finish/coating: | Uncoated |
| number of rows: | 1 |
| closure type: | Open |
| internal clearance: | C3 |
| outer ring width: | 48 mm |
| ring separation: | Non-Separable |
| fillet radius: | 2 mm |
| operating temperature range: | Maximum of +300 ° F |
| series: | NCF29 |
| | |



GARLOCK BEARINGS LTD

dynamic load capacity:

583 kN