



GARLOCK BEARINGS LTD



71806 ACD/P4 Bearing 2D drawings and 3D CAD models

71806 ACD/P4 SKF High Speed Angular Contact Ball Bearings

Bearing No. 71806 ACD/P4

Size	42x30x7 mm
Bore Diameter	42 mm
Outer Diameter	30 mm
Width	7 mm
d	30 mm
D	42 mm
B	7 mm
d ₁	34.1 mm
d ₂	34.1 mm
D ₁	38.1 mm
r _{1,2} - min.	0.3 mm
r _{3,4} - min.	0.15 mm
a	11.9 mm
d _a - min.	32 mm
d _b - min.	32 mm
D _a - max.	40 mm
D _b - max.	41.2 mm
r _a - max.	0.3 mm
r _b - max.	0.15 mm
d _n	34.5 mm
Basic dynamic load rating - C	4.2 kN
Basic static load rating - C ₀	3.6 kN
Fatigue load limit - P _u	0.15 kN
Limiting speed for grease	28000 r/min



GARLOCK BEARINGS LTD

Lubrication	
Limiting speed for oil lubrication	45000 mm/min
Ball - D_w	3.175 mm
Ball - z	23
G_{ref}	0.24 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	37 N
Preload class B - G_B	110 N
Preload class C - G_C	220 N
Calculation factor - f	1.14
Calculation factor - f_1	0.97
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.08
Calculation factor - f_{2C}	1.15
Calculation factor - f_{HC}	1
Preload class A	69 N/micron
Preload class B	106 N/micron
Preload class C	144 N/micron
d_1	34.1 mm
d_2	34.1 mm
D_1	38.1 mm
$r_{1,2}$ min.	0.3 mm



GARLOCK BEARINGS LTD

$r_{3,4}$ min.	0.15 mm
d_a min.	32 mm
d_b min.	32 mm
D_a max.	40 mm
D_b max.	41.2 mm
r_a max.	0.3 mm
r_b max.	0.15 mm
d_n	34.5 mm
Basic dynamic load rating C	4.16 kN
Basic static load rating C_0	3.55 kN
Fatigue load limit P_u	0.15 kN
Attainable speed for grease lubrication	28000 r/min
Attainable speed for oil-air lubrication	45000 r/min
Ball diameter D_w	3.175 mm
Number of balls z	23
Reference grease quantity G_{ref}	0.24 cm ³
Preload class A G_A	37 N
Static axial stiffness, preload class A	69 N/ μ m
Preload class B G_B	110 N
Static axial stiffness, preload class B	106 N/ μ m
Preload class C G_C	220 N
Static axial stiffness, preload class C	144 N/ μ m
Calculation factor f	1.14
Calculation factor f_1	0.97
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.08
Calculation factor f_{2C}	1.15
Calculation factor f_{HC}	1



GARLOCK BEARINGS LTD

Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.026 kg